

**Manually Operated (Micrometer)**

Our largest capacity hand machine with horizontal annular head and simple calibration



Option of air hydraulic foot pedal operation
(80-100 PSI air supply required)

- Hose Capacity 3/16" - 1.1/2" (2 Wire) & up to 1.1/4" R9R/4SP (4Wire)
- Simple calibration system with easy to insert dies

Product features and specifications

Hose capacity	3/16" - 1 1/2" R1AT & R2AT (2 wire) and up to 1 1/4" R9R/4SP (4 wire)
Crimping range	See die chart information below
Crimping force	1750 kN
Operation	Twin speed hand pump with integral relief valve
Calibration	Simple dial adjusted calibrator
Pump rating	317 Bar (4,600 psi)
Additional die sets available	For 1 piece fittings, Freon, PTFE & other special applications
Packed Dimensions / Net Weight / Gross Weight	790mm x 650mm x 550mm / 75 kgs / 94 kgs

H32MM Die Chart (mm) *Non standard dies

Die No	Range (mm)	Die Length	Ferrule Dia Max	Die No	Range (mm)	Die Length	Ferrule Dia Max
*H06	06.0-07.9	40	18	*H26	26.0-29.9	50	38
*H08	08.0-09.9	40	20	H28	28.0-33.9	60	40
*H10	10.0-12.9	40	22	*H30	30.0-33.9	60	42
*H13	13.0-15.9	40	25	H34	34.0-39.9	70	46
H16	16.0-21.9	40	28	H40	40.0-45.9	70	52
H19	19.0-21.9	40	31	H46	46.0-51.9	75	58
H22	22.0-25.9	50	34	H52	52.0-57.9	75	64

Tel: 01472 255928

Email: hello@hydraulicmegastore.com